



PRODUCT DESCRIPTION

Description Self-adhered, waterproof membrane with acrylic pressure sensitive adhesive, designed for sealing on difficult-to-stick-to surfaces. This tape is temperature tolerant and adheres to damp surfaces.

Material Film backing lined with acrylic adhesive.



PRODUCT PROPERTIES

Dimensions 50 mm (2") x 22.8 m (75 ft) roll

Adhesion Properties (ASTM D-3330)

Polyethylene/Polypropylene:
60 oz./in. width (66 N/100 mm)

Anodized Aluminium:
After 7 days at 176°F:
70 oz./in. width (77 N/100 mm)
After 7 days in water:
65 oz./in. width (71 N/100 mm)
After Thermal Cycling:
75 oz./in. width (82 N/100 mm)
After UV Exposure:
60 oz./in. width (66 N/100 mm)

Permeability (ASTM E-96 desiccant method) 0.17 perms

Nail Sealability (ASTM E331/547 as modified per AAMA 711-07 Annex 1)
Initial: Pass
After Thermal Cycling: Pass

Tape Thickness (ASTM D-3652) 9.9 mils (0.25 mm)

Service Temp. Range (Tested per AAMA 711-05) -40 to -176°F (-40 to 80°C)

Application Temp Range 0 - 120°F (-18 to 49°C)